



## DIRECTIONALS



### SecuriLED II SERIES

#### Surface Mount

The SecuriLED II™ is the new generation of Directional LED lamps following the popular SecuriLED. They encompass enhanced styling, features and improved performance. The units are interchangeable with the original SecuriLED, sharing similar dimensions and the same fixing hole size and centres.

The low-profile LED lamp has a more modern and ergonomic design featuring a non-corrosive bezel and is resistant to humidity and vibration. The SecuriLED II™ is fully sealed against moisture and dust ingress meeting IP67. They are particularly suited to larger vehicles and situations where a 'BIG' warning signal is desired, e.g. Trucks, Road Sweepers, Agricultural Trailers etc.

Available in multiple colours, R65 Category X Class II approved with multiple flash patterns which are selectable and multiple units can be synchronised.

#### Features and Benefits

- Seven flash patterns
- Synchronisable with additional units
- Temperature Range: -30°C to +55°C
- Colour options: 
- R65 Class II Approved
- Feature a non-corrosive bezel
- Polycarbonate base & lens
- Units sealed against moisture and dust ingress
- Dimensions:  
118mm (H) x 130mm (W) x 21.5mm (D)

#### Models

PART NO.	COLOUR	VOLTAGE	AMPS	MOUNT
ED5110A	Amber	12-24	1.2	Surface
ED5110B	Blue	12-24	1.2	Surface
ED5110R	Red	12-24	0.7	Surface
ED5110W	White	12-24	0.9	Surface