

# T-TAPE FOAM MASKING TAPE

## TECHNICAL DATA SHEET 1019


V1. 01/25

### PRODUCT DESCRIPTION

T-Tape Foam Masking Tape is designed for aperture masking of the inner surface of vehicle access points to reduce the ingress and build-up of paint during the automotive finishing process.

It offers good conformity around contours; a custom-formulated adhesive providing clean, residue-free removal; dual foams providing strength from the flat base foam and a graduated painting edge from the upper foam.

### PRODUCT CONSTRUCTION



### SHELF LIFE

12 months from date of receipt by customer when stored at 22°C (72°F) and 50% relative humidity.

### PHYSICAL PROPERTIES

Values shown are typical values and should not be used for specification purposes.

|            |                                  |
|------------|----------------------------------|
| Upper Foam | Low density open cell foam       |
| Base Foam  | High density closed cell XL foam |
| Adhesive   | Rubber-based                     |
| Liner      | Single-side coated paper         |
| Colour     | White                            |
| Width      | 10mm (±15%)                      |
| Length     | 25m (±5%)                        |

### PERFORMANCE PROPERTIES

Values shown are typical values and should not be used for specification purposes.

|                     |         |
|---------------------|---------|
| Peel Adhesion       | 3.0N    |
| Elongation at Break | ≥120%   |
| Tensile Strength    | ≥100kPa |

Tel: +44 (0)1625 618185 | [www.jtape.com](http://www.jtape.com) | [info@jtape.com](mailto:info@jtape.com)

Designed & Manufactured in the UK: Hulley Road, Macclesfield, Cheshire, SK10 2SF.

#TAPESMART

Important Notice to Purchaser: JTAPE MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. User is responsible for determining whether the JTAPE product is fit for a particular purpose and suitable for user's application. Please remember that many factors can affect the use and performance of a JTAPE Automotive product in a particular application. The materials to be bonded to the product, the conditions in which the product is used, and the time and environmental conditions, in which the product is expected to perform are among the many factors that can affect the use and performance of a JTAPE Automotive product, some of which are uniquely within the user's knowledge and control. It is essential that the user evaluate the JTAPE Automotive product to determine whether it is fit for a particular purpose and suitable for user's methods of application. Limitation of Remedies and Liability: If the JTAPE product is proved to be defective, THE EXCLUSIVE REMEDY, AT JTAPE'S OPTION, SHALL BE TO REFUND THE PURCHASE PRICE OF OR TO REPAIR OR REPLACE THE DEFECTIVE JTAPE PRODUCT. JTAPE shall not otherwise be liable for loss or damages, whether direct, indirect special, incidental, or consequential, regardless of the legal theory asserted, including negligence, warranty, or strict liability.