

SPRAYGUN CLEANER

Spraygun cleaner

::: DESCRIPTION

- Solvent-based paint spray gun cleaner

::: AREA OF APPLICATION

- Cleaning of paint spray guns
- Removal of contamination from water- and solvent-based paints

::: BENEFITS

- Easy and thorough cleaning
- Enormous time saving
- Cost-effective alternative to the spray gun cleaning machine

::: PRODUCT DATA

Material data

Colour:	transparent
Container:	400 ml aerosol can
VOC:	267 g
Storage life:	10 years in a closed container at 20°C





SPRAYGUN CLEANER

Spraygun cleaner

V01
09/2022

:: HANDLING

APPLICATION		
	<p>Processing</p>	<ul style="list-style-type: none"> ▪ Give can a quick shake ▪ Carry out spray test ▪ Disassemble spray gun immediately after painting and thoroughly spray to wash away all paint residues ▪ Wipe with a clean, dry non-woven / paper towel ▪ Leave cleaned parts to dry thoroughly
	<p>End of work</p>	<p>When work is finished, reverse aerosol and spray valve empty.</p>
DISPOSAL		
<p>Please mind the residue inside the containers. Completely emptied containers can be used for recycling. If cans are not emptied, they should be disposed off as „special refuse“.</p>		

:: REMARKS

Personal protection is required:

- Respirator Mask type: A2/P2
- Eye protection: protective safety glasses
- Protective gloves, e.g. made of latex or nitrile

FOR PROFESSIONAL USE ONLY.

SPRAYGUN CLEANER

Spraygun cleaner

::: STORAGE AND TRANSPORT CONDITIONS

Protect from freezing, heat, sunlight and moisture. Store tightly closed in a dry, cool place. Recommended storage and transportation temperature range is: +18 to +25°C. Avoid extreme temperature fluctuation.

Note: The storage and transportation temperature must be not lower than +5°C. Acclimatize the product to room temperature naturally.

2004/42/IB (e)(670) <670: The EU limit value for this product (product category: IB.e) in ready to use form is max. 670 g/litre of VOC

::: REMARKS

Allow the product to reach the recommended application temperature naturally (avoid rapid heating/ cooling). It is not recommended to apply the product at a temperature below 18°C.

SAFETY ISSUES

The before mentioned technical data and information, especially the recommendations for applying and using our products, are based on our current knowledge and experience when applied under normal conditions.

In practice, the materials, surfaces or site conditions are so different that no warranty regarding the working results or liability, arising out of any relationship, can be inferred neither from this information nor from a verbal consultation, except we are charged with intent or gross negligence. In this case the user is obliged to prove that he has informed us about all points required for a proper and promising judgement in writing, in time and completely. Patent rights of any third party are to be observed. Furthermore, our general sales and delivery Terms and Conditions and the latest Technical Data Sheet, which should be demanded, apply.

Directions for handling and waste disposal are in our Material Safety Data Sheet and the specifications of the Employers Liability Insurance Association for the chemical industry.

Copyright VOSSCHEMIE